

TL-E-03-03D 41/9


INPUT VOLTAGE **230~240VAC**

OUTPUT VOLTAGE **3VDC**

ELECTRICAL & MECHANICAL SPECIFICATION



OUTPUT POWER CORD:
2468 20AWG/2C
+5.5*2.1*12mm (I) PLUG



ELECTRONICAL SPECIFICATION

Input Voltage	230~240	Volts
Frequency (Hz)	50	Hz
Power Rated (W)	10	W
Exciting Current With No load	50	mA Max
Exciting Current With Full load	80	mA Max
Output Voltage (DC)	3.0	Volts±5%
Output Current	1.0	Amp
Output Voltage Without Load	7.2	Volts±5%

HI-POT :

Test Time	1	Min
PRI TO SEC	3750	Volts
PRI TO CORE	3750	Volts
SEC TO CORE	1250	Volts
Insulation Class	B (130)	°C

MECHANICAL SPECIFICATION

Dimensions (L*W*H)	76.5*48.5*40.0	mm
Weight	320	g
Environment:		
Operating Temperature	-10 To 40	°C
Storage Temperature	-20 To 70	°C
Relative Temperature	40 ±2	°C
RELATIVE HUMIDITY	90% RH	

Output Cable: **2468 20AWG/2C 105 °C 1.8M**
LENGTH + 5.5*2.1*12mm (I) PLUG

ELECTRICAL CIRCUIT

