

Robot Top Series TSS-276 Series



Conductor			Number of Cores	PVC Insulation		撚線外徑O.D.	PVC Jacket	
nominal cross-section area. (mm ²)	strand NO./diameter of conductor	O.D.		Thickness	O.D.		Thickness	O.D.
0.5	100/0.08	0.95	2	0.6	2.2	4.4	1.0	6.5
	100/0.08	0.95	3	0.6	2.2	4.8	1.0	6.8
	100/0.08	0.95	4	0.6	2.2	5.3	1.0	7.3
	100/0.08	0.95	5	0.6	2.2	6.0	1.0	8.1
	100/0.08	0.95	6	0.6	2.2	6.6	1.0	8.7
	100/0.08	0.95	7	0.6	2.2	7.3	1.1	9.6
	100/0.08	0.95	8	0.6	2.2	8.0	1.2	10.5
	100/0.08	0.95	10	0.6	2.2	8.8	1.3	11.5
	100/0.08	0.95	12	0.6	2.2	9.2	1.4	12.1
	100/0.08	0.95	16	0.6	2.2	10.7	1.5	14.0
	100/0.08	0.95	24	0.6	2.2	13.5	1.6	16.8
0.75	150/0.08	1.2	2	0.6	2.4	4.8	1.0	6.9
	150/0.08	1.2	3	0.6	2.4	5.2	1.0	7.3
	150/0.08	1.2	4	0.6	2.4	5.8	1.0	7.9
	150/0.08	1.2	5	0.6	2.4	6.5	1.0	8.6
	150/0.08	1.2	6	0.6	2.4	7.2	1.1	9.5
	150/0.08	1.2	7	0.6	2.4	8.0	1.2	10.5
	150/0.08	1.2	8	0.6	2.4	8.7	1.3	11.4
	150/0.08	1.2	10	0.6	2.4	9.6	1.4	12.5
	150/0.08	1.2	12	0.6	2.4	10.0	1.4	12.9
	150/0.08	1.2	16	0.6	2.4	11.7	1.5	15.0
	150/0.08	1.2	24	0.6	2.4	14.7	1.6	18.0
1.25	4/60/0.08	1.5	2	0.6	2.7	5.4	1.0	7.5
	4/60/0.08	1.5	3	0.6	2.7	5.8	1.0	7.9
	4/60/0.08	1.5	4	0.6	2.7	7.3	1.1	9.6
	4/60/0.08	1.5	6	0.6	2.7	8.1	1.2	10.6
	4/60/0.08	1.5	8	0.6	2.7	9.8	1.4	12.7
	4/60/0.08	1.5	12	0.6	2.7	11.2	1.5	14.3
	4/60/0.08	1.5	16	0.6	2.7	13.2	1.5	16.3
	4/60/0.08	1.5	24	0.6	2.7	16.6	1.6	19.9

TSS-276

2	4/100/0.08	1.9	2	0.6	3.1	6.2	1.0	8.3
	4/100/0.08	1.9	3	0.6	3.1	6.7	1.0	8.8
	4/100/0.08	1.9	4	0.6	3.1	7.5	1.1	9.8
	4/100/0.08	1.9	6	0.6	3.1	9.3	1.4	12.2
	4/100/0.08	1.9	8	0.6	3.1	11.2	1.5	14.3
	4/100/0.08	1.9	12	0.6	3.1	12.9	1.5	16.0
	4/100/0.08	1.9	16	0.6	3.1	15.1	1.6	18.4
3.5	7/100/0.08	2.8	2	0.8	4.4	8.1	1.3	11.5
	7/100/0.08	2.8	3	0.8	4.4	9.5	1.4	12.4
	7/100/0.08	2.8	4	0.8	4.4	10.6	1.5	13.7
	7/100/0.08	2.8	5	0.8	4.4	11.9	1.5	15.0
	7/100/0.08	2.8	6	0.8	4.4	13.2	1.5	16.3
	7/100/0.08	2.8	7	0.8	4.4	14.5	1.6	17.8
	7/100/0.08	2.8	8	0.8	4.4	15.9	1.6	19.2
	7/100/0.08	2.8	10	0.8	4.4	17.6	1.6	20.9
5.5	7/150/0.08	3.1	2	1.0	5.1	10.5	1.4	13.1
	7/150/0.08	3.1	3	1.0	5.1	11.0	1.5	14.1
	7/150/0.08	3.1	4	1.0	5.1	12.3	1.5	15.4
	7/150/0.08	3.1	5	1.0	5.1	13.8	1.6	17.1
	7/150/0.08	3.1	6	1.0	5.1	15.3	1.6	18.6
	7/150/0.08	3.1	7	1.0	5.1	16.9	1.6	20.2
	7/150/0.08	3.1	8	1.0	5.1	18.4	1.6	21.7

