

ROBOT TOP RO-VS-SS SERIES TSS-276a Series



Conductor			Number of Cores	PVC Insulation		撚線外徑 O.D.	Braid Shielding		PVC Jacket
nominal cross-section area. (mm ²)	strand NO./diameter of conductor	O.D.		Thickness	O.D.		構成本數Core/線徑 Core/diameter	O.D.	Thickness
0.5	100/0.08	0.95	2	0.6	2.2	4.4	120/0.12TA	4.8	1.0
	100/0.08	0.95	3	0.6	2.2	4.8	120/0.12TA	5.1	1.0
	100/0.08	0.95	4	0.6	2.2	5.3	120/0.12TA	5.6	1.0
	100/0.08	0.95	5	0.6	2.2	6.0	160/0.12TA	6.4	1.0
	100/0.08	0.95	6	0.6	2.2	6.6	160/0.12TA	7.0	1.0
	100/0.08	0.95	7	0.6	2.2	7.3	160/0.12TA	7.7	1.1
	100/0.08	0.95	8	0.6	2.2	8.0	160/0.12TA	8.4	1.2
	100/0.08	0.95	10	0.6	2.2	8.8	160/0.12TA	9.2	1.3
	100/0.08	0.95	12	0.6	2.2	9.2	208/0.12TA	9.3	1.4
	100/0.08	0.95	16	0.6	2.2	10.7	208/0.12TA	11.1	1.5
	100/0.09	0.95	20	0.6	2.2	11.7	240/0.12TA	12.1	1.5
100/0.08	0.95	24	0.6	2.2	13.5	240/0.12TA	13.6	1.6	
0.75	150/0.08	1.2	2	0.6	2.4	4.8	120/0.12TA	5.2	1.0
	150/0.08	1.2	3	0.6	2.4	5.2	160/0.12TA	5.6	1.0
	150/0.08	1.2	4	0.6	2.4	5.8	160/0.12TA	6.2	1.1
	150/0.08	1.2	5	0.6	2.4	6.5	160/0.12TA	6.9	1.1
	150/0.08	1.2	6	0.6	2.4	7.2	160/0.12TA	7.6	1.1
	150/0.08	1.2	7	0.6	2.4	8.0	160/0.12TA	8.4	1.1
	150/0.08	1.2	8	0.6	2.4	8.7	160/0.12TA	9.1	1.3
	150/0.08	1.2	10	0.6	2.4	9.6	208/0.12TA	10.0	1.4
	150/0.08	1.2	12	0.6	2.4	10.0	208/0.12TA	10.4	1.5
	150/0.08	1.2	16	0.6	2.4	11.7	208/0.12TA	12.1	1.5
	150/0.09	1.2	20	0.6	2.4	12.7	240/0.12TA	13.1	1.5
150/0.08	1.2	24	0.6	2.4	14.7	240/0.12TA	14.9	1.5	
	4/60/0.08	1.5	2	0.6	2.7	5.4	120/0.12TA	5.8	1.0
	4/60/0.08	1.5	3	0.6	2.7	5.8	160/0.12TA	6.2	1.0

1.25	4/60/0.08	1.5	4	0.6	2.7	6.5	160/0.12TA	6.9	1.1
	4/60/0.08	1.5	6	0.6	2.7	8.1	160/0.12TA	8.5	1.2
	4/60/0.08	1.5	8	0.6	2.7	9.2	208/0.12TA	10.2	1.4
	4/60/0.08	1.5	12	0.6	2.7	11.2	240/0.12TA	11.6	1.5
	4/60/0.08	1.5	16	0.6	2.7	13.2	240/0.12TA	13.6	1.5
2	4/100/0.08	1.9	2	0.6	3.1	6.2	160/0.12TA	6.6	1.0
	4/100/0.08	1.9	3	0.6	3.1	6.7	160/0.12TA	7.1	1.0
	4/100/0.08	1.9	4	0.6	3.1	7.5	160/0.12TA	7.9	1.1
	4/100/0.08	1.9	6	0.6	3.1	9.3	208/0.12TA	9.7	1.4
	4/100/0.08	1.9	8	0.6	3.1	11.2	208/0.12TA	11.6	1.5
	4/100/0.08	1.9	12	0.6	3.1	12.9	240/0.12TA	13.3	1.5
3.5	7/100/0.08	2.8	2	0.8	4.4	8.8	160/0.12TA	9.2	1.3
	7/100/0.08	2.8	3	0.8	4.4	9.5	208/0.12TA	9.9	1.4
	7/100/0.08	2.8	4	0.8	4.4	10.6	208/0.12TA	11.0	1.5
	7/100/0.08	2.8	5	0.8	4.4	11.9	208/0.12TA	12.3	1.5
	7/100/0.08	2.8	6	0.8	4.4	13.2	240/0.12TA	13.6	1.5
	7/100/0.08	2.8	7	0.8	4.4	14.5	240/0.12TA	14.9	1.6
5.5	7/150/0.08	3.1	2	1.0	5.1	10.2	208/0.12TA	10.6	1.4
	7/150/0.08	3.1	3	1.0	5.1	11.0	240/0.12TA	11.4	1.5
	7/150/0.08	3.1	4	1.0	5.1	12.3	240/0.12TA	12.7	1.5
	7/150/0.08	3.1	5	1.0	5.1	13.8	240/0.12TA	14.2	1.6