



# Hollow Shaft Gearmotor

Telco's Rugged & Reliable Hollow Shaft gearmotor offers a wide speed ranges in a compact size. It is specially designed for ice agitator, gate opener and furnace applications. It's ideal for tight space application, while requires exceptional torque. The output torque can reach up to 1100 in-lb, with the motor power ranging from 1/80 HP to 1/10HP in both AC and DC. The insulation class F (155° C) provides the gearmotor better protection for the high humidity and moisture environment. The hollow shaft design can be optional with single or double output shafts, and the output shaft diameter can go up to 1" in diameter. For more information (standard/customized options), please contact us.

## Specifications

### Gearhead

Housing: Precision machined die cast aluminum  
 Shafts: Hardened Steel  
 Bearings : Needle and ball bearings

### Motor

AC: 1/40, 1/25, 1/20, 1/15, 1/10,HP  
 DC: 12V ~ 48V available  
 Insulation: Class F  
 Finish: Powder-coat gloss black

### Current Available Model:

- \* 115 VAC, 60Hz, 1/20 HP, 4rpm @ 906-lb
- \* 12VDC, 2.4rpm@1093in-ob



9812 Whithorn Dr.,  
 Houston, TX 77095,  
 Phone: 281.855.2218  
 Fax: 281.859.8825  
 Website: [www.telcointercon.com](http://www.telcointercon.com)  
 Email: [motors@telcointercon.com](mailto:motors@telcointercon.com)

