


FAN AND BLOWER

- Available in a comprehensive line of cooling products, including AC & DC fans, fan motors and blowers.
- Fan products range from 15x15x4mm to 280x280x89mm in size and furnished in standard ball bearing and sleeve bearing. Many fans are also furnished in fluid dynamic bearing or rifle bearing.
- Blowers include AC blower, DC blower, centrifugal blowers, sirocco fan blowers, and are available from 0.09 cubic feet per minute (CFM) airflow to 250 CFM.
- Many of our fan/blower products were listed under UL, CUL, CSA, TUV, and CE. Some models also available with VDE.
- Applications: HVAC, food equipment, vehicle, electronic cooling, exhaust blowers, wood stoves, fireplace inserts and draft inducers.



AC Fan

- Sizes from 60x60x30mm to 280x280x89mm
- Running on 100~120VAC and 220~240VAC
- Available in ball bearing and sleeve bearing
- Available in wire type and terminal type Options including fluid dynamic bearing, plastic housing and metallic housing, as well as different impeller configurations.



DC Fan

- Available in various sizes ranging from 15x15x4mm to Ø254x849mm
- Furnished in standard fluid dynamic bearing or sleeve bearing models Run on 5, 12, 24 or 48 VDC
- Used in power supplies those are eventually delivered to computer manufacturers, audio and video industries.



Fan Motor

- Wide range of fan motor choices including outer rotor fan motor, condenser fan motor, centrifugal fan motor and more, so you can freely choose the model that's perfect for your application.
- Design for energy efficient and durable.



Blower

- Wide ranges of AC blowers, DC blowers, centrifugal blowers, sirocco fan blowers and others
- The maximum air flow of our blower products range from 0.09 cubic feet per minute (CFM) airflow to 250 CFM.
- Bearing type includes rifle, dual-ball or sleeve.



Telco Intercontinental Corp.

9812 Whithorn Dr., Houston TX 77095
(281)855-2218 hvac@telcointercon.com
www.telcointercon.com

TELCO
MOTION