

Low Cost PMDC - Flat Sided



15.5mm Series

Applications

- * Locking System
- * CD Player
- * MD Player
- * CD Player Tracking
- * Motorized Curtain



Specification

Model No.	Voltage		No-Load		At Maximum Efficiency					Stall Torque
	Operating Range	Nominal	Speed	Current	Speed	Current	Torque	Output	Efficiency	
	V	V	RPM	A	RPM	A	gf.cm	W	%	
PL16FF3-2-01D	1.0~2.0	1.5	6730	0.1	4700	0.23	3.00	0.14	42.0	10
PL16FF3-3-01	1.8~3.5	2.6	4480	0.04	3250	0.08	2.20	0.07	35.3	8.0
PL16FF3-3-02	2.0~4.0	3.0	9200	0.07	7350	0.18	2.50	0.18	34.9	12.4
PL16FF3-5-04	3.0~6.0	5.0	10200	0.05	7500	0.16	4.50	0.35	43.3	17.0
PL16FF3-5-01	3.0~6.0	5.0	6050	0.02	4540	0.05	2.00	0.09	37.3	8.0
PL16FF3-10-01	6.0~12.0	10.0	7650	0.02	5300	0.05	2.00	0.11	22.0	6.5
PL16FF3-12-01	6.0~12.0	12.0	9000	0.02	7000	0.05	2.00	0.14	23.3	9.0

Model No.	Voltage		No-Load		At Maximum Efficiency					Stall Torque
	Operating Range	Nominal	Speed	Current	Speed	Current	Torque	Output	Efficiency	
	V	V	RPM	A	RPM	A	gf.cm	W	%	
PL16FF3-2-05	1.0~3.0	1.5	7500	0.13	5000	0.69	10.00	0.51	49.0	30.0
PL16FF3-3-07V	1.5~4.5	3.0	9600	0.09	6450	0.41	10.00	0.66	53.7	30.0
PL16FF3-5-04	3.0~7.0	5.0	8700	0.06	6790	0.17	6.00	0.42	49.4	27.4
PL16FF3-7-06V	5.0~9.0	7.0	10300	0.06	8500	0.17	7.00	0.61	51.0	42.0
PL16FF3-8-03	6.0~12.0	8.0	7630	0.02	6040	0.07	5.00	0.31	55.3	24.0
PL16FF3-12-05V	6.0~18.0	12.0	9000	0.02	7100	0.09	7.00	0.5	60.0	33.1
PL16FF3-12-02V	6.0~18.0	12.0	5000	0.02	3440	0.04	5.00	0.17	36.7	16.0
PL16FF3-14-06V	6.0~18.0	13.5	10670	0.03	8250	0.09	6.20	0.55	45.0	28.6

Outline Drawing

